

Flexible LED Strip Lighting



Product Name

Rhea Series

Model

R0060AQ

Applications

Suitable for cove and contour lighting etc. in KTV, hotel, shopping mall, home, cabinet and so on.

Features

- 1. 1. 5050SMD LED mounted;
- 2. 2.Can be cut at the printed marks;
- 3. 3. Certification: UL, CE, RoHS;

Installation

- 1. Easy installation with double-sided adhesive tape;
- 2. Many installation and fixing options available with the minimum bending diameter as 5cm[1.96in];

Warranty

3 years or 13,000 hours, whichever comes first.



Flexible LED Strip Lighting

Optical and Electrical Parameters

P/N	LED Color	Color Temperature(K) Wavelength(nm)	Beam Angle (°)	Luminous Flux (lm/m)	CRI	Luminous Efficacy (Im/W)	Working Voltage (V DC)	Working Current (mA)		Power (W)	
								1m [39.37in]	5m [196.85in]	1m [39.37in]	5m [196.85in]
	Red	620-625	1	120	72.00				101	十十	
R0060AQ	Green	525-530	115	180		STHO	12	1200	4000	14.4	48
121	Blue	465-470	1/	60					<u> </u>		1

Others

P/N	LED Color	Standard Length		Max. Length		LED Qty	Operating Temperature		Storage Temperature		ΙP
		(m)	(FT)	(m)	(FT)	(pcs/ m)	()	(°F)	()	(°F)	Grade
R0060AQ	RGB	5	16.4	5	16.4	60	-25~+60	-13~140	-25~+70	-13~158	IP33

Notes:

- □ Testing environment temperature: 25±2°C [77±3.6°F];
- The above luminous flux is based on the monochromatic strip;

Profile Drawings


Unit mm [in]

			51.51[2.03]	_ 16.7 0 [0 .657]	
-E-1	200.0[7.874]	4544		5000.0[196.85]	10.0[0.394]
		11 4			2.1[0.083]



Flexible LED Strip Lighting

Packaging Diagram



Packaging Information:

- 1. 5m [196.85in] per reel, 40 reels per outer carton;
- 2. Outer Carton: 45*25*25.6 cm=0.0288 (1±10%) CBM [17.72*9.84*10.08in]
- 3. Net Weight (N.W): 2.7 (1±10%) kg [5.952 (1±10%) lb];
- 4. Gross Weight (G.W): 5.4 (1±10%) kg [11.905 (1±10%) lb];
- 5. The actual packed quantity and weight subject to change without prior notice.